



E-CUBE 8 Dia

Product Specification

V1.3 Rev01

Physical specification

- Width: 532 mm
- Depth: 787 mm
- Height: 1470~1560 mm (Monitor Folded: 1190 mm)
- Weight: 55 kg (System only)

System design

- 21.5" flat panel monitor and new articulated arm
- Front handle
- Up/Down Module
- 4 active probe connectors
- 1 pencil probe port
- 4 swivel wheels
- Integrated SSD with HDD
- ECG (Optional)
- Built-in stereo speaker
- Built-in cable management
- System boot-up: in 60 sec

Main monitor

- 21.5" high definition LED backlit LCD
- Resolution: 1,920 x 1,080 (16:9 wide)
- 16.2M color display
- Contrast: 1:1,000
- IPS (In Plane Switching) technology
- Bright and contrast adjustment
- Image Filter
- Articulated monitor arm
 - Swivel: +/- 135°
 - Tilt: +30° / -90°

Control panel

- Alphanumeric keyboard with backlit
- Ergonomic key layout
- 8 TGC control levers
- 3 user customizable keys
- 5 probe holders with 2 removable
- Optional built-in gel warmer (3 temperature levels)
 - Low: 31° C
 - Medium: 34° C
 - High: 37° C

Touch screen

- 10.4" high definition LED backlit LCD
- Resolution: 1,024 X 768
- 16.2M color display
- Bright and contrast adjustable (OSD)

Computing power

- Main processor: Intel core i3-6100E 2.7 GHz
- Main memory: 4 GB
- SSD[120GB] and HDD[1TB]

Electrical specification

- 100 - 120 V, 220-240 V, 50/60 Hz
- Power consumption: Max. 900 VA

System architecture

- Digital beamforming
- High density transducer connector
- Power View™ (C- Architecture) of transducer
- Triple multi-beam
- Flexcan™
- SensitiView™
- Crystal Signature™
- MicroFit™
- Optimal Imaging Suite™
- Raw data processing
- Needle enhancement
- Windows7 Embedded

Transducer type

- Convex
- Micro convex
- Endo cavity
- Linear
- Phased (Sector)
- Volume

Application

- Abdomen
- Appendix
- Breast
- Cardiac
- EM
- Gynecology
- Musculoskeletal
- Obstetrics
- Pediatric
- Small Parts
- Urology
- Vascular

Preset

- Abdomen
- Abdomen (Pen)
- Appendix (Bowel)
- Renal
- OB1, OB2, OB3
- Fetal Echo
- Thyroid
- Testicle
- MSK
- Superficial
- MSK deep
- Nerve
- Shoulder/Knee
- Wrist/Elbow
- Breast
- EM
- Vascular
- Cardiac
- Cardiac (Pen)
- TCD

Imaging mode

- 2D (B)
- Color Doppler (CF)
- Pulse Wave Doppler (PW)
- Power Doppler (PD)
- Directional Power Doppler (DPDI)
- Tissue Doppler Imaging (TDI)
- Continuous Wave Doppler (CW)
- Motion (M)
- Color M
- Anatomical M
- 3D/4D
- Live HQ™
- Panoramic
- Elastography
- Needle Vision™ / Needle Vision™ Plus
- Dual Live

Complex mode

- Duplex: B+B, B+PW, B+CW, B+CF, B+PD, B+DPDI, B+M, B+3D, B+4D, B+Live HQ, A+B+C+3D, A+B+C+4D, B+Elastography
- Triplex: B+CF+PW, B+CF+CW, B+CF+M

Scanning parameters

- System frequency range: 1 ~ 20 MHz
- Processing channel: 786,432
- ADC: 12 bits
- Displayed imaging depth: 0 ~ 40 cm
- Max. Frame rate (Probe dependent)
 - 2D: over 2,099 (Hz/FPS)
 - Color: 351 (Hz/FPS)
 - Volume: 45 (Hz/VPS)
- Dynamic range: Max. 250 dB
- Gray scale: 256 levels
- Max. Scan line: 1,638
- Focus
 - Focal number: Max.8
 - Focal position: Max. 20
- Zoom
 - Write zoom: Max. 11.9x (probe dependent)
 - Read zoom: Max. 10x
- CF (Probe dependent)
 - 0.3 kHz - 13.2 kHz
 - 0.3 cm/s - 4.82 m/s
- PW (Probe dependent)
 - 0.3 kHz - 26.0 kHz
 - 0.7 cm/s - 114 m/s
- CW
 - 0.1 kHz - 69.4 kHz
 - 0.3 cm/s - 305 m/s

Image presentation

- Dual
- Quad
- Duplex image format
 - 1:1 / 1:2 / 2:1 / full screen
- Image reverse: Left/right
- Image rotation: 0°, 90°, 180°, 270°

Display annotation

- Patient ID: Up to 64 characters
- Patient name: First, last and middle
- Gender, age and birth date
- Gestational age from LMP, EDD and GA
- Transducer name
- Institution / hospital name: up to 25 characters
- Date format: 3 types
 - YYYY/MM/DD
 - MM/DD/YYYY
 - DD/MM/YYYY
- Time format: 2 types
 - 12 hours / 24 hours
- Acoustic power

- Mechanical index (MI)
- Thermal index (TI): TIS, TIB, TIC
- Transducer name
- Preset
- Transducer orientation
- Depth
- Focus
- TGC line
- Frequency
- Frame rate
- Power
- Mode name
- Gray scale bar
- Arrow
- Indicator
- Text
 - Size: 1 ~ 10
- Body pattern
 - 201 sets
 - Size: small, medium, large
- Biopsy guide line
- Thumbnail
- Stored image info
- Cine gauge
- Measurement result

Live mode display

- 2D
 - Angle steer (Probe dependent): 7 steps (-20 ~ 20°)
 - Colorize: 0 ~ 25
 - Dynamic range: 30 ~ 250 dB
 - Edge enhance: 0 ~ 10
 - Frequency: 5 steps
 - Full SRI: 0 ~ 5
 - Gray map: 0 ~ 43(Probe dependent)
 - Gain: 0 ~ 100
 - Harmonic
 - Pulse inversion harmonic
 - Invert
 - Line density: 0 ~ 5
 - Persistence: 0 ~ 4
 - Power: 1 ~ 100%
 - Reject: 1 ~ 10
 - Spatial compounding : 0 ~ 5
 - Frequency compounding
- M
 - Anatomical M: On, off
 - AMM angle
 - Colorize: 0 ~ 25
 - Dynamic range: 30 ~ 250dB
 - Gray map: 0 ~ 43(Probe dependent)
 - Gain: 0 ~ 100
 - Reject: 0 ~ 10

- Power: 1 ~ 100%
- Sweep speed: 0 ~ 6
- PWD
 - Angle: -89° ~ 89°
 - Angle steer (Probe dependent): 7 steps (-20 ~ 20°)
 - Auto angle
 - Base line: -8 ~ 8
 - Colorize: 0 ~ 22
 - Dynamic range: 30 ~ 120dB
 - Frequency: 3 steps
 - Gray map: 0 ~ 18(Probe dependent)
 - Gain: 0 ~ 100
 - Line density: 0 ~ 5
 - Power: 1 ~ 100%
 - Reject: 0 ~ 10
 - Scale (PRF): 0.3 ~ 20.1 kHz (Probe dependent)
 - SV size: 0.2 ~ 25mm
 - Sweep speed: 0 ~ 6
 - Sound: 0 ~ 100%
 - Wall filter: 0 ~ 9
- CWD
 - Angle: -89° ~ 89°
 - Base line: -8 ~ 8
 - Dynamic range: 30 ~ 120dB
 - Gray map: 0 ~ 22
 - Gain: 0 ~ 100
 - Scale (PRF): 0.3 ~ 69.4 kHz (Probe dependent)
 - Frequency: 2 steps
 - Power: 1 ~ 100%
 - Reject: 0 ~ 10
 - Sound: 0 ~ 100%
 - Sweep speed: 0 ~ 6
 - Wall filter: 0 ~ 9
- CF/PD
 - Angle steer (probe dependent): 7 steps (-20 ~ 20°)
 - Base line: -100 ~ 100
 - Color map: 0 ~ 28 (CF), 0 ~ 8 (PD), 0 ~ 9 (DPDI)
 - Ensemble: 6 ~ 16
 - Frequency: 3 steps
 - Flow state: Low, mid, high
 - Gain: 0 ~ 100
 - Line density: 0 ~ 2
 - Power: 1 ~ 100%
 - Scale (PRF): 0.3 ~ 10.4 kHz (probe dependent)
 - Smooth: 0 ~ 10
 - Wall filter: 0 ~ 7
- 3D/4D (Volume Master™)
 - Quality: Low, Mid, H1, H2
 - Volume angle: 10 ~ 120° (probe dependent)
 - Curved ROI
 - View direction: Up, down, Lt, Rt, front, back
 - Brightness: 1 ~ 100
 - Contrast: 1 ~ 100

- Threshold: 0 ~ 255
- Opacity: 0 ~ 255
- Smooth: 0 ~ 20
- SRI (2D): 0 ~ 5
- Gray map: 0 ~ 30
- 2D Colorize: 0 ~ 25
- 3D Color Map: 1 ~ 18
- MPR
 - Display format
 - Ref. Plane
 - 3D Orientation
 - Edit ROI
 - Volume Sync (Vol. Sync)
 - Render Setup: Surface, MaxIP, MinIP, XRay, Light, Live HQ
- Cine Calc.
- Initializing (init.)
- Easy cut
- Sectional Planes
 - Multi Plane
 - Cubic View: Box / Niche / Plane
- Multi Slice
 - Display format: 1*1 / 1*2 / 2*2 / 3*3 / 4*4
 - Reference plane
 - Active view
 - Guide view
 - Pitch: 0 ~ 35 mm
 - Previous / Next
- Live HQ™
 - Live HQ setup
 - Light Direction
 - Move light
 - Live HQ color map: Skin 1 ~ 12
 - HQ Scatter: 0 ~ 10
 - Front scale: -20 ~ 20
 - Back scale: -20 ~ 20
- Volume Advance™
 - AnySlice
 - Display format
 - Reference line (Ref. Line)
 - New / Undo / Delete All
 - Thickness: 0 ~ 20mm
 - Free Angle MSV
 - Display format: 1*1 / 1*2 / 2*2 / 3*3 / 4*4
 - Reference plane
 - Active view
 - Guide view
 - Pitch: 0 ~ 35 mm
 - Previous / Next
 - Volume Analysis
 - Disc thickness: 1 / 2 / 5 / 8 / 10 mm
 - Display format
 - Propagation Disc / Volume Display off

- Current plane disc
 - Disc Transparency: 0 ~ 1 (10 steps)
 - Delete / Delete All
- Panoramic
 - Colorize: 0 ~ 25
 - Dynamic range: 30 ~ 250 dB
 - Edge enhancement: 0 ~ 4
 - Frequency: 3 steps
 - Full SRI: 0 ~ 5
 - Gray map: 0 ~ 37
 - Gain: 0 ~ 100
 - Harmonic
 - Pulse inversion harmonics
 - Line density: 0 ~ 5
 - Persistence: 0 ~ 5
 - Power: 1 ~ 100%
 - Reject: 1 ~ 9
- Elastography
 - Live dual: On / off
 - Invert: On / off
 - E persistence: 1 ~ 4
 - Alpha blending: 0 ~ 100
 - Color map: 0 ~ 8
- Needle Vision plus
 - L/R Flip
 - Angle: Shallow, Medium, Steep

Post processing

- 2D
 - Colorize
 - Dynamic range
 - Edge Enhance
 - Full SRI
 - Gain
 - Gray map
 - Reject
 - TGC
- M
 - Colorize
 - Dynamic range
 - Gain
 - Gray map
 - Reject
 - Sweep speed
- PWD
 - Angle correction
 - Auto Calc.
 - Baseline
 - Colorize
 - Dynamic range
 - Gain
 - Gray map

- Invert
- Reject
- Sweep speed
- CWD
 - Angle correction
 - Auto Calc.
 - Baseline
 - Colorize
 - Dynamic range
 - Gray map
 - Reject
 - Sweep speed
- CF/PD
 - Baseline
 - Blend / Adaptive blend
 - Colorize
 - Color map
 - Invert (CF / DPDI)
 - Threshold

- Tissue Doppler Imaging (TDI)
- Volume Master™
- Live HQ™
- Volume Advance™
- Cube View™
- Cube Strain™
- Stress Echo
- Needle Vision™
- Needle Vision™ Plus
- 4 probe port
- ECG (IHE / AHA)
- Foot switch (3 pedals)
- Wireless LAN
- Side basket
- Cube note

Imaging technology

- Filtered Tissue Harmonic Imaging (FTHI)
- Pulse Inversion Tissue Harmonic Imaging (PTHI)
- Speckle Reduction Imaging (SRI)
- Full Speckle Reduction Imaging (Full SRI)
- Needle Vision™
- Needle Vision™ Plus
- Xpeed™
- Live HQ™
- Beam steer
- Virtual convex (Trapezoidal)
- Elastography
- Panoramic
- Automated intima media thickness measurement

Image archive

- Raw data image processing
- Post processing
- E-View™
- 1TB internal hard drive reserved for patient data
- Image store
 - Up to 170,000 images (without compression)
 - Up to 1,350,000 images (with JPG compression)
- Image format
 - BMP, JPEG, DICOM, AVI, WMV
- Export (Send To) / Backup / Restore
- Network storage
- Cube View™

Features

- Auto NT
- Auto IMT
- CV measure & report
- SRI
- Full SRI
- Xpeed™
- Spatial Compounding
- Filtered Tissue Harmonic Imaging (FTHI)
- Continuous Wave (CW)
- DICOM
- DICOM SR: OB, Adult Echo, Vascular, Breast
- Anatomical M
- Panoramic
- Elastography

Cine

- Cine memory: 450 MB, 28,800 frames, 128 volumes, 300 sec
- Prospective and retrospective
- Cine review, save and edit
- Run, stop, frame move
- Play speed: 50% 100%, 200%, 300%, 400%

Transducers

SC1-4H

- Convex array
- Frequency: 1.0 - 4.0 MHz
- Field of view: 60°
- Elements: 192
- Radius of curvature: 60 mm
- Footprint: 72.4 X 16.8 mm
- Application: Abdomen, EM, Gynecology, Obstetrics
- Crystal Signature™ Technology
- Biopsy available

SC1-4HS

- Convex array
- Frequency: 1.0 - 4.0 MHz
- Field of view: 73°
- Elements: 166
- Radius of curvature: 46 mm
- Footprint: 68 X 15.9 mm
- Application: Abdomen, EM, Gynecology, Obstetrics
- Crystal signature™ technology
- Biopsy available

SC1-6H

- Convex array
- Frequency: 1.0 - 6.0 MHz
- Field of view: 60°
- Elements: 192
- Radius of curvature: 60 mm
- Footprint: 72.4 X 16.8 mm
- Application: Abdomen, EM, Gynecology, Obstetrics
- Crystal signature™ technology
- Biopsy available

C1-6CT

- Convex array
- Integrated with C-architecture Technology
- Frequency: 1.0 - 6.0 MHz
- Field of view: 60°
- Elements: 128
- Radius of curvature: 60 mm
- Footprint: 71.6 x 16.8 mm
- Application: Abdomen, EM, Gynecology, Obstetrics
- Crystal signature™ technology
- Biopsy available

VC1-6T

- Convex array (Volume)
- Frequency: 1.0 - 6.0 MHz
- Field of view: 79°
- Sweep angle: 75°
- Radius of curvature: 40 mm
- Elements: 128
- Footprint: 59.2 X 45.2 mm
- Application: Abdomen, OB, GYN, EM
- Biopsy is not available

C5-8NT

- Micro convex array
- Frequency: 5.0 - 8.0 MHz
- Field of view: 93.6°
- Elements: 128
- Radius of curvature: 15 mm
- Footprint: 25.5 X 9 mm
- Application: Abdomen, EM, Cardiac, Pediatric

L3-12H

- Linear array
- Frequency: 3.0 - 12.0 MHz
- Field of view: 38.4 mm
- Elements: 192
- Footprint: 44.8 X 7.8 mm
- Application: Breast, EM, MSK, Vascular, Small Parts, Appendix
- Biopsy available

L8-17H

- Linear array
- Frequency: 8.0 - 17.0 MHz
- Field of view: 38.4 mm
- Elements: 192
- Footprint: 44.8 X 7.8 mm
- Application: Breast, EM, MSK, Vascular, Small Parts
- Biopsy available

IO8-17T

- Linear array
- Frequency: 8.0 - 17.0 MHz
- Field of view: 25.6 mm
- Elements: 128
- Footprint: 36.7 X 4.2 mm
- Application: Small Parts, MSK

- Biopsy is not available

L3-12H^{WD}

- Linear array
- Frequency: 3.0 - 12.0 MHz
- Field of view: 57.0 mm
- Elements: 192
- Footprint: 64.0 x 8.4 mm
- Application: Breast, EM, MSK, Vascular, Small Parts, Appendix
- Biopsy not available

L3-12T

- Linear array
- Frequency: 3.0 - 12.0 MHz
- Field of view: 38.4 mm
- Elements: 128
- Footprint: 44.8 X 7.8 mm
- Application: Breast, EM, MSK, Vascular, Small Parts, Appendix
- Biopsy available

P1-5CT

- Phased array
- Frequency: 1.0 - 5.0 MHz
- Field of view: 90°
- Elements: 64
- Footprint: 23 X 13.4 mm
- Application: Abdomen, Cardiac, EM, TCD
- Crystal signature™ technology
- Biopsy is not available

SP3-8T

- Phase array
- Frequency: 3.0 - 8.0 MHz
- Field of view: 90°
- Elements: 64
- Footprint: 16 X 12.8 mm
- Application: Abdomen, Cardiac, EM, Pediatric
- Crystal signature™ technology
- Biopsy is not available

EV3-10T

- Endo Cavity
- Frequency: 3.0 - 10.0 MHz
- Field of view: 142°
- Elements: 128
- Footprint: 21.5 X 18.6 mm
- Application: GYN, OB, Fetal Echo, Urology, EM
- Biopsy available

EC3-10T

- Endo Cavity
- Frequency: 3.0 - 10.0 MHz
- Field of view: 142°
- Elements: 128
- Footprint: 21.5 X 18.6 mm
- Application: GYN, OB, Fetal Echo, Urology, EM
- Biopsy available

CW2

- Pencil
- Frequency: 2.0 MHz
- Footprint: 17.2 x 17.2 mm
- Application: Cardiac
- Biopsy is not available

CW5

- Pencil
- Frequency: 5.0 MHz
- Footprint: 10.3 x 10.3mm
- Application: Cardiac
- Biopsy is not available

VE3-10H

- Endo cavity (Volume)
- Frequency: 3.0 - 10.0 MHz
- Field of view: 160°
- Sweep angle: 120°
- Radius of curvature: 10 mm
- Elements: 192
- Footprint: 24.4 X 24.4 mm
- Application: GYN, OB, Urology
- Biopsy available

Measurement and Calculation

Basic (Caliper)

- Distance
- Area Circumference
- %Stenosis
- Volume
- Angle
- A/B ratio
- Volume Flow Area
- Time
- Slope
- HR
- Velocity
- Acceleration
- S/D Ratio
- PI
- RI
- Trace
- Auto Trace
- VTI

Abdomen measurement

- Aorta
- Renal
- Renal A
- Renal V
- Hepatic A
- IVC
- Hepatic V
- Mid HV
- MPV
- Portal V
- Splenic A
- Splenic V
- SMA
- SMV
- IMA
- Iliac A
- Iliac V
- Vessel
- HR

Breast measurement

- Mass 1 ~ 10
- Duct dilatation
- Breast Flow
- HR

Cardiology measurement

- Ao/LA
- LA Vol (Diam)
- Aorta Diam
- Pul. Diam
- Vena Cava
- RV
- Simpson BP
- Simpson SP
- Modified Simpson
- Area Length
- Teichholz
- LV Mass T-E
- LV Mass A-L
- LA Vol (A-L)
- LA Vol (Simpson)
- RA Vol (A-L)
- RA Vol (Simpson)
- TV
- PISA
- MV
- AV
- PV
- Qp/Qs
- Pul. Vein
- TDI
- HR

Gynecology measurement

- Uterus
- Ovary
- Follicle
- Fibroid
- Pelvic Floor
- Early Gestation
- Ovarian
- Uterine
- FHR
- Ovarian A
- Uterine A
- Vessel
- Aorta
- Umbilical A
- Placenta
- Des. Aorta
- HR

Obstetrics measurement

- Early Gestation
- Fetal Biometry
- Fetal Long Bones
- Fetal Cranium
- Fetal Others
- Maternal Others
- Generic
- AFI
- CRAR
- 4 Chamber view
- Aortic Arch
- LVOT
- Outflow tract
- RVOT
- Thorax
- Venous
- FHR
- Tricuspid Valve
- Mitral Valve
- Main Pulmonary A
- Aorta
- Ductus Art
- Umbilical A
- Umbilical V
- Ductus Ven
- Pulmonary Valve
- Aortic Valve
- Pulmonary Vein
- Carotid
- MCA
- SMA
- Celiac A
- Uterine A
- IVC

Emergency Medicine measurement

- Aorta
- Renal
- Bladder
- %Stenosis
- A/B ratio
- SMA
- IMA
- IVC
- Uterine A
- Ovarian A
- Vessel
- HR

MSK measurement

- Volume
- HIP (BA) / Hip (AB)
- Vessel
- HR

Pediatric measurement

- Aorta
- Renal
- Renal A
- CHA
- IVC
- Hepatic V
- Mid HV
- MPV
- Portal V
- Splenic A
- Splenic V
- SMA
- SMV
- IMA
- Iliac A
- Iliac V
- Vessel
- Hip
- HR

Renal measurement

- Renal L
- Renal
- Aorta
- Renal A
- Portal V
- Vessel
- HR

Small Parts measurement

- Thyroid
- Isthmus
- Nodule
- Lymph Node
- Parathyroid
- Thyroid Flow
- Testicle
- Testicle Flow
- HR

Urology measurement

- Renal
- Bladder
- Testicle
- Prostate
- Residual
- Vessel
- Bladder
- HR

Vascular measurement

- CCA
- ICA
- ECA
- Bulb
- Vert. A
- Subclav. A
- Axill. A
- Basilar A
- Brach. A
- DBA
- Basilic A
- Radial A
- Ulnar A
- SPA
- Innom. A
- IJA
- Subclav. V
- Ceph. V
- Brach. V
- DBV
- Basilic V
- Radial V
- Ulnar V
- Innom. V
- CIA
- EIA
- IIA
- CFA
- DFA
- SFA
- Pop. A
- PTA
- ATA
- Peron. A
- DPA
- Prof. A
- CIV
- EIV
- IIV
- CFV

- DFV
- SFV
- GSV
- LSV
- Pop. V
- PTV
- ATV
- Peron. V
- DPA
- Prof. A
- MCA
- ACA
- PCA P1
- PCA P2
- Vert. A
- Basilar A
- PComA
- AComA
- Renal A
- Renal V
- Segm. A
- Interlob. A
- Arcuate A
- ABD. Aorta
- SMA
- IMA
- Hepatic A
- Portal V
- Splenic A
- Straight Gft
- Loop Gft
- Cimino Gft
- Comp Gft
- HR

Connectivity

Peripheral

- USB 2.0 (4 ports)
- USB 3.0 (2 ports)
- Ethernet 10/100 Base-T
- Remote control
- DVI out
- VGA (D-Sub) out
- S-VHS out
- Composite video out
- BNC out
- Audio in L/R
- Audio out L/R

DICOM

- DICOM 3.0
- Image storage
- Multi-frame image storage
- Secondary image capture storage
- Structured report (OB, Cardiology, Vascular)
- Grayscale print management
- Color print management
- Storage commitment push model
- Modality performed procedure step
- Worklist
- Verification
- Media storage: USB media, DVD, CD-R

Thermal printers

- BW
 - Sony UP-D898MD
 - Sony UP-X898MD
 - Mitsubishi P95DE
- Color
 - Sony UP-D25MD
 - Sony UP-25MD

- EN 61000-4-2:2009 (IEC 61000-4-2:2008)
- EN 61000-4-3:2006 + A1:2008 + A2:2010 (IEC 61000-4-3: 2006 + A1:2007 + A2:2010)
- EN 61000-4-4:2012 (IEC 61000-4-4:2012)
- EN 61000-4-5:2014 (IEC 61000-4-5:2005)
- EN 61000-4-6:2014 (IEC 61000-4-6:2008)
- EN 61000-4-8:2010 (IEC 61000-4-8:2009)
- EN 61000-4-11:2004 (IEC 61000-4-11:2004)
- EN 61000-3-2:2014 (IEC 61000-3-2: 2014)
- EN 61000-3-3:2013 (IEC 61000-3-3:2013)
- EN 62304:2006 /AC:2008 (IEC 62304:2006)
- EN 62366:2008 /A1:2015 (IEC 62366:2014)
- EN ISO 14971:2012 (ISO 14971:2007)
- ETSI EN 301 489-1 V1.9.2:2011
- ETSI EN 301 489-17 V2.2.1:2012
- EN ISO 10993-1:2009 (ISO 10993-1:2009)
- EN ISO 10993-5:2009 (ISO 10993-5:2009)
- EN ISO 10993-10:2013 (ISO 10993-10:2010)
- AIUM/NEMA UD 2:2004 (R2009)
- AIUM/NEMA UD 3:2004 (R2009)
- MDD 93/42/EEC
- CANADA [Regulation] SOR-98-282
- CE
- WEEE
- Rohs

Safety and Compliance

- IEC/EN 60601-1:6.8.1:
 - Type of protection against electrical shock: Class I
 - Degree of protection against electrical shock (Patient connection): Type BF equipment
 - Degree of protection against harmful ingress of water: Ordinary equipment and all of applied parts (IPX7, IPX8) except ECG meet ingress protection level according to IEC 60529.
 - Degree of safety of application in the presence of a flammable anesthetic material with air or with oxygen or nitrous oxide: Equipment not suitable for use in the presence of a flammable anesthetic mixture with air or with oxygen or nitrous oxide.
 - Mode of operation: Continuous operation
- EN 60601-1:2006 + A11:2011+A1:2013 (IEC 60601-1:2005 + A1:2012)
- EN 60601-1-2:2007+AC:2010 (IEC 60601-1-2:2007)
- EN 60601-1-6:2010/A1:2015 (IEC 60601-1-6:2010+A1:2013)
- EN 60601-2-37: 2008 + A11:2011 (IEC 60601-2-37:2007)
- EN 55022:2010/AC:2011, Class B (CISPR 22:2008, modified)
- EN 55011:2009 + A1:2010, Group 1, Class B

© 2017 ALPINION MEDICAL SYSTEMS – All rights reserved.

2017 ALPINION MEDICAL SYSTEMS reserves the right to make changes in specifications and features shown hereby, or discontinue the product described at any time without notice or obligation. Contact you ALPINION representative or the most current information.